



MATERIAL
 Front Panel: SPCC black powder coating finish, t=0.063 in= 1.6 mm = 15 ga
 Rear Panel: SPCC, plated with zinc, t=0.063 in= 1.6 mm= 15 ga
 Cable Manager: SPCC black powder coating finish, t=0.063 in= 1.6 mm = 15 ga

Coupler
 Housing: High-impact Acrylonitrile Butadiene Styrene (ABS resin), UL 94 V-0 rated
 Jack Contacts: 5100W spring temper phosphor bronze round wire, Ø=0.018 in (0.45 mm), plated with 50 µin (1.27 µm) minimum thick hard gold over 100 µin (2.54 µm) minimum thick nickel underplate
 Contact Holder: High-impact Polycarbonate (PC resin), UL 94 V-0 rated
 PCB: FR4, UL 94 V-0 rated
 RoHS compliant

INCLUSION

NO.	Item	Q'ty
1	Screw	4
2	Introduction	1



DRAWN BY Autumn Lee		Another quality product from BLACK BOX 724-746-8300 • www.blackbox.com	
APPROVED BY Jerry Su		TITLE Feed-Through CAT6 Unshielded Patch Panel-48-Port	
DIMENSIONS ARE [IN (MM)] TOLERANCES:		PARTS NO. JPM820A	
~0.8"	~2"	~6"	6"~
ANGLE	2"		
±0.007"	±0.015"	±0.02"	±0.06"
3rd Angle Projection	DATE 2010/11/11		
SCALE X		SHEET 1/1	
REV. 1			