

CAT5e 45-Degree Angled Patch Panel

Fits where space is limited.



Specifications

Frame: 16-gauge metal

Front Ports: RJ-45 female angled 45 degrees downward

IDC Contacts: 50 microinch gold plated over tin plating

Rear Contacts: IDC contacts, compatible with both 110 and Krone tool

RJ-45 Contacts: 50 microinch gold plated over nickel plating

Wire Gauge: Supports 22 to 26 AWG both solid or stranded

Wiring: Supports both T568A and T568B

Size: JPM5E24-45ANG: 1.75" (1U) high (4.5 cm);

JPM5E48-45ANG: 3.5" (2U) high (9 cm)

Weight: JPM5E24-45ANG: 1.15 lb. (0.52 kg);

JPM5E48-45ANG: 2 lb. (0.9 kg)

Overview

This Category 5e, 45-degree angled patch panel is different from a typical patch panel. The ports are angled downward at a 45-degree angle. These angled panels can be used in applications where space is limited. They meet the industry standard ANSI/TIA/EIA 568C.2 specifications for Category 5e.

What's Included

Your package should contain the following items. If anything is missing or damaged, contact Black Box at 724-746-5500.

JPM5E24-45ANG:

- 24-port panel
- (4) 10-32 screws
- (4) 12-24 screws
- (6) small cable ties
- This user's manual

JPM5E48-45ANG:

- 48-port panel
- (4) 10-32 screws
- (4) 12-24 screws
- (12) small cable ties
- This user's manual

TRADEMARKS USED IN THIS MANUAL

Black Box and the Double Diamond logo are registered trademarks of BB Technologies, Inc.

Any other trademarks mentioned in this manual are acknowledged to be the property of the trademark owners.



© Copyright 2009. All rights reserved.

FREE, live, 24/7 Tech Support is just 20 seconds away.
724-746-5500 | blackbox.com