



General Spec:

- CABLE: Magnalium Braid OD5.2mm (0.2 inches) Black.
- Color: BLACK.
- Connector 1: DSP Shell Nickel Plated Contact Gold Plated 15u".
- Connector 2: DSP Shell Nickel Plated Contact Gold Plated 15u".
- Wire AWG: 32 Gauge
- Supports data-transfer rates of up to 5.4Gbps for high-resolution digital displays.
- Max resolutions: 3840 x2160 (30 bpp @ 60Hz) May vary by Montiors' type and video adaptors.
- Use for real-time digital audio and video transfers and plug-and-play device installation.
- DisplayPort 1.1 standards.
- Support 1080P Resolution.
- Cable Marking: DisplayPort Cable AWM E101344 STYLE 20276 80°C 30V VW-1 SPACE SHUTTLE-D
- RoHS Compliant Certified

Part Number	Product Length L(ft)
VCB-DP-0003-MM	3
VCB-DP-0006-MM	6
VCB-DP-0010-MM	10
VCB-DP-0015-MM	15

Pin Out

P1	P2	P1	P2
1 White	12	15 White	15
3 Brown	10	17 Black	17
2 Drain	11	16 Drain	16
4 White	9	13 Red	13
6 Red	7	14 Orange	14
5 Drain	8	18 Yellow	18
7 White	6	19 White	19
9 Green	4	Shell Braid	Shell
8 Drain	5		
10 White	3		
12 Blue	1		
11 Drain	2		

UNLESS OTHERWISE SPECIFIED TOLERANCE			
ANG.	±		
0.	±	SCALE: NONE	UNIT: Inch
.0	±	APPLICATION NO.: VCB-DP-xxxx-MM	
.00	±	DRAWN: 04/27/'12	Descriptions: Display port Cable Male to Male
		CHECKED: / /	PRODUCT NO.:
		APPROVED: / /	FILE NAME: TBD
		SIZE: A4	REV. X2

SHEET NO.
1 of 2